

TECHINICAL DATA SHEET

WB-221 SATIN

PRODUCT DESCRIPTION

Sanitred's WB 221 SATIN is a low sheen finish, two-component water based, 55% solids, aliphatic polyurethane. WB 221 Satin is easy to apply and is extremely hard and abrasion resistant, chemical, and hot tire resistant. Low VOC and Low odor.

STANDARD COLORS: Clear
OTHER COLORS ALSO AVAILABLE: N/A

CURE SCHEDULE (70°)

POT LIFE (1.5 GAL Volume)	N/A
TACK FREE (DRY TO TOUCH)	5-7 hours
RECOAT OR TOPCOAT	6-12 hours
LIGHT FOOT TRAFFIC	18-24 hours
HEAVY FOOT TRAFFIC	5 days

COVERAGE

Recommended for use as a topcoat on epoxy, concrete, plywood, and Graniflex Broadcast Systems,

COVERAGE PER GALLON: 175-300 square feet per gallon

MIX RATIO: 2 Parts A to 1 Part B

RECOMMENDED FILM THICKNESS: 5-8 mils

PACKAGING INFORMATION: 1.5 gallon kits

PHYSICAL PROPERTIES

FLEXURAL STRENGTH: N/A
COMPRESSIVE STRENGTH: N/A
TENSILE STRENGTH: N/A
ADHESION: Concrete Failure
VISCOSITY: N/A
ABRASION RESISTANCE: N/A
ULTIMATE ELONGATION: N/A
HARDNESS: N/A
VOLATILE ORGANIC CONTENT: < 100 grams/liter
SHELF LIFE: 1 year in unopened containers

CHEMICAL RESISTANCE

REAGENT	RATING
URINE	D
XYLENE	D
MEK	B
ISOPROPYL ALCOHOL	D
METHANOL	D
GASOLINE	D
SKYDROL	D
BRAKE FLUID	D
NITRIC ACID 10%	A
HYDROCHLORIC ACID 20%	D

RATING KEY: A - NOT RECOMMENDED, B - CONDITIONAL, C - RECOMMENDED CONDITIONAL, D - RECOMMENDED,
NOTE: EXTENSIVE CHEMICAL RESISTANCE INFORMATION IS AVAILABLE THROUGH YOUR SALES REPRESENTATIVE.

TECHNICAL DATA SHEET

WB-221 SATIN

LIMITATIONS

Will freeze during storage. Store at temps above 40F

On grade slabs must perform a moisture-vapor transmission test.

Surfaces must be dry, clean and free of foreign matter. Clear coating may turn opaque and cloudy due to moisture penetration, especially exterior.

Surfaces may be slippery when wet.

WARNING: This product contains isocyanates

Using proper ventilation if used indoors

Do not apply when substrate temperature is below 50 degrees or above 85 degrees

Apply in thin coats

Do not thin the product

Do not apply less than 350 square foot per gallon or film properties will be impaired

INSTRUCTIONS

PRODUCT MIXING: Premix Part A and Part B individually. Measure out desired amount needed. Mix 1 Part B into 2 Part A and mix thoroughly for 3 minutes.

SURFACE PREPARATION: Refer to the TCP Training manual and the ICRI standards for proper surface preparation.

CLEANUP: Use acetone solvents

FLOOR CLEANING: Caution! Some cleaners may affect the color of the floor installed. Test each cleaner in a small area, utilizing your cleaning technique. If no ill effects are noted, you can continue to clean with the product and process tested.

RESTRICTIONS: Restrict the use of the floor to light traffic and non-harsh chemicals until the coating is fully cured (see technical data under full cure). It is best to let the floor remain dry for the full cure cycle.

NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY

The Concrete Protector (Division of Incredible Products, LLC), warrant that all products are assembled under rigorous quality assurance specifications and that all information supplied is exact. All information supplied is not to be taken as a warranty, but for you to conduct your own test to determine if the given product is suitable for your distinct purpose. The following list of properties should not be interpreted as specifications. CONVEYED OR SUGGESTED, NO WARRANTY IS BUILT UPON ANY DISCOVERED RESULTS OR INFORMATION YOU WILL OBTAIN DURING USE. CONVEYED OR SUGGESTED NO WARRANTY IS BUILT THAT THE GIVEN PRODUCT SHALL BE MARKETABLE OR THAT THE GIVEN PRODUCT WILL BE FIT FOR ANY DISTINCT PURPOSE. NO WARRANT IS BUILT UPON SAID INFORMATION OR THAT THE GIVEN PRODUCT WILL NOT INFRINGE UPON ANY PATENT. The Concrete Protector is NOT liable for, direct or indirect, inadvertent or consequential damages. The Concrete Protector's liability is and will only be limited to the net selling price of our products or, at our discretion, the replacement of our products. Upon delivery of our products, your acceptance means that you accept all terms of this warranty even if other documents and or purchase orders astray from the terms of this warranty. No representative, on our behalf, is permitted to make any representation, warranty, or assume liability with any sale of our products. OUR PRODUCTS CONTAIN CHEMICALS THAT CAN CAUSE SERIOUS PHYSICAL INJURY. BEFORE THE USE OF OUR PRODUCTS, READ ALL MATERIAL AND FOLLOW ALL LISTED PRECAUTIONS TO AVOID ANY BODILY HARM