



TECHNICAL DATA SHEET

Hydrophobic Sealer

PRODUCT DESCRIPTION

The Concrete Protector's Hydrophobic Sealer is a water dilutable silicone water repellent that imparts penetrating water repellency for treatment of concrete, masonry and stone construction materials.

STANDARD COLORS: Milky White

CURE SCHEDULE (70°)

POT LIFE (1.5 GAL Volume)	N/A
TACK FREE (DRY TO TOUCH)	N/A
RECOAT OR TOPCOAT	N/A
LIGHT FOOT TRAFFIC	N/A
FULL CURE	28 days

COVERAGE

Recommended for imparting water repellency to porous construction materials such as brick, stone, concrete blocks, mortar and grout.

COVERAGE PER BOTTLE:	170-200 sq ft per gal mixed 425-500 sq ft per concentrated
MIX RATIO:	9 Parts Water to 1 Bottle
RECOMMENDED FILM THICKNESS:	N/A

PACKAGING INFORMATION: 32 ounce bottle

PHYSICAL PROPERTIES

- FLEXURAL STRENGTH:** N/A
- COMPRESSIVE STRENGTH:** N/A
- TENSILE STRENGTH:** N/A
- ADHESION:** N/A
- VISCOSITY:** N/A
- ABRASION RESISTANCE:** N/A
- ULTIMATE ELONGATION:** N/A
- HARDNESS:** N/A
- VOLATILE ORGANIC CONTENT:** <100 g/l
- SHELF LIFE:** 12 months in unopened container

CHEMICAL RESISTANCE

REAGENT	RATING

RATING KEY: A - NOT RECOMMENDED, B - 2 HOUR TERM SPLASH SPILL, C - 8 HOUR TERM SPLASH SPILL, D - 72 HOUR IMMERSION, E - LONG TERM IMMERSION.
NOTE: EXTENSIVE CHEMICAL RESISTANCE INFORMATION IS AVAILABLE THROUGH YOUR SALES REPRESENTATIVE.

FEATURES

Low VOC meets California South Coast AQMD requirements

Fast Beading Action

Excellent Water Repellency

Water-Based Easy to Use

Dilutable, Dilution Stable

Effective at Concentration as low as 3% Actives

No SiH vented containers not required

INSTRUCTIONS

PRODUCT MIXING: 9 Parts Water to 1 Bottle CP Hydrophobic Sealer

SURFACE PREPARATION: Refer to the TCP Training manual and the ICRI standards for proper surface preparation.

CLEANUP: N/A

FLOOR CLEANING: Caution! Some cleaners may affect the color of the floor installed. Test each cleaner in a small area, utilizing your cleaning technique. If no ill effects are noted, you can continue to clean with the product and process tested.

RESTRICTIONS: Restrict the use of the floor to light traffic and non-harsh chemicals until the coating is fully cured (see technical data under full cure). It is best to let the floor remain dry for the full cure cycle.

NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY

The Concrete Protector (Division of Incredible Products, LLC), warrant that all products are assembled under rigorous quality assurance specifications and that all information supplied is exact. All information supplied is not to be taken as a warranty, but for you to conduct your own test to determine if the given product is suitable for your distinct purpose. The following list of properties should not be interpreted as specifications. CONVEYED OR SUGGESTED, NO WARRANTY IS BUILT UPON ANY DISCOVERED RESULTS OR INFORMATION YOU WILL OBTAIN DURING USE. CONVEYED OR SUGGESTED NO WARRANTY IS BUILT THAT THE GIVEN PRODUCT SHALL BE MARKETABLE OR THAT THE GIVEN PRODUCT WILL BE FIT FOR ANY DISTINCT PURPOSE. NO WARRANTY IS BUILT UPON SAID INFORMATION OR THAT THE GIVEN PRODUCT WILL NOT INFRINGE UPON ANY PATENT. The Concrete Protector is NOT liable for, direct or indirect, inadvertent or consequential damages. The Concrete Protector's liability is and will only be limited to the net selling price of our products or, at our discretion, the replacement of our products. Upon delivery of our products, your acceptance means that you accept all terms of this warranty even if other documents and or purchase orders astray from the terms of this warranty. No representative, on our behalf, is permitted to make any representation, warranty, or assume liability with any sale of our products. OUR PRODUCTS CONTAIN CHEMICALS THAT CAN CAUSE SERIOUS PHYSICAL INJURY. BEFORE THE USE OF OUR PRODUCTS, READ ALL MATERIAL AND FOLLOW ALL LISTED PRECAUTIONS TO AVOID ANY BODILY HARM