



TECHNICAL DATA SHEET

SUPER NOVA

PRODUCT

The Concrete Protector Super Nova is a two component, high solids, colored novolac epoxy.

STANDARD COLORS: Light Grey, Med Grey, Red

OTHER COLORS ALSO AVAILABLE: N/A

CURE SCHEDULE (70°)

POT LIFE (1.5 GAL Volume) 20-35 mins

TACK FREE (DRY TO TOUCH) 4-8 hours

RECOAT OR TOPCOAT 4-10 hours

LIGHT FOOT TRAFFIC 9-18 hours

FULL CURE 28 days

COVERAGE

Recommended for areas where a medium build topcoat is needed.

COVERAGE PER GALLON: 85-100 sq ft @ 15-19 mils

MIX RATIO: 1 Gallon Part A to 0.5 Gallon Part B by volume

RECOMMENDED FILM THICKNESS: 15-19 mils

PACKAGING INFORMATION: 3 Gallon and 15 Gallon Kits

PHYSICAL PROPERTIES

FLEXURAL STRENGTH: 9,500 psi @ ASTM D790

COMPRESSIVE STRENGTH: N/A

TENSILE STRENGTH: N/A

ADHESION: 425 psi

VISCOSITY: 2100-2600 cps

ABRASION RESISTANCE: 19 mg loss

ULTIMATE ELONGATION: N/A

HARDNESS: D=85

VOLATILE ORGANIC CONTENT: 0.40# per gallon

SHELF LIFE: 1 year in unopened containers

CHEMICAL RESISTANCE

REAGENT	RATING
MEK	C
METHANOL	C
ETHYL ALCOHOL	C
70% SULFURIC ACID	C
1,1,1, TRICHLOROETHANE	C
SKYDROL	C
5% ACETIC ACID	D
XYLENE	D
10% HYDROCHLORIC ACID	D
10% SODIUM HYDROXIDE	E
50% SODIUM HYDROXIDE	E
10% SULFURIC ACID	E

RATING KEY: A - NOT RECOMMENDED, B - 2 HOUR TERM SPLASH SPILL, C - 8 HOUR TERM SPLASH SPILL, D - 72 HOUR IMMERSION, E - LONG TERM IMMERSION.

NOTE: EXTENSIVE CHEMICAL RESISTANCE INFORMATION IS AVAILABLE THROUGH YOUR SALES REPRESENTATIVE.

LIMITATIONS

For best results, apply a 3/8" nap roller.

Substrate temperature must be 5°F above dew point.

All new concrete must be cured for at least 30 days prior to application.

Color stability or gloss may be affected by environmental conditions such as high humidity or chemical exposure.

Physical properties are typical values and not specifications.

Colors may vary from batch to batch.

This product is not UV color stable and may discolor when exposed to UV lighting.

INSTRUCTIONS

PRODUCT MIXING: Kits come premeasured. Mix ratio 1 Gallon Part A to 0.5 Gallon Part B

SURFACE PREPARATION: Refer to the TCP Training manual and the ICRI standards for proper surface preparation.

CLEANUP: Use xylol

FLOOR CLEANING: Caution! Some cleaners may affect the color of the floor installed. Test each cleaner in a small area, utilizing your cleaning technique. If no ill effects are noted, you can continue to clean with the product and process tested.

RESTRICTIONS: Restrict the use of the floor to light traffic and non-harsh chemicals until the coating is fully cured (see technical data under full cure). It is best to let the floor remain dry for the full cure cycle.

NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY

The Concrete Protector (Division of Incredible Products, LLC), warrant that all products are assembled under rigorous quality assurance specifications and that all information supplied is exact. All information supplied is not to be taken as a warranty, but for you to conduct your own test to determine if the given product is suitable for your distinct purpose. The following list of properties should not be interpreted as specifications. CONVEYED OR SUGGESTED, NO WARRANTY IS BUILT UPON ANY DISCOVERED RESULTS OR INFORMATION YOU WILL OBTAIN DURING USE. CONVEYED OR SUGGESTED NO WARRANTY IS BUILT THAT THE GIVEN PRODUCT SHALL BE MARKETABLE OR THAT THE GIVEN PRODUCT WILL BE FIT FOR ANY DISTINCT PURPOSE. NO WARRANTY IS BUILT UPON SAID INFORMATION OR THAT THE GIVEN PRODUCT WILL NOT INFRINGE UPON ANY PATENT. The Concrete Protector is NOT liable for, direct or indirect, inadvertent or consequential damages. The Concrete Protector's liability is and will only be limited to the net selling price of our products or, at our discretion, the replacement of our products. Upon delivery of our products, your acceptance means that you accept all terms of this warranty even if other documents and or purchase orders astray from the terms of this warranty. No representative, on our behalf, is permitted to make any representation, warranty, or assume liability with any sale of our products. OUR PRODUCTS CONTAIN CHEMICALS THAT CAN CAUSE SERIOUS PHYSICAL INJURY. BEFORE THE USE OF OUR PRODUCTS, READ ALL MATERIAL AND FOLLOW ALL LISTED PRECAUTIONS TO AVOID ANY BODILY HARM